

Covered wagon with tarpaulin top, 75m³, Tams



Vorteile

- Weather-resistant tarpaulin makes it suitable for weather-sensitive bulk goods
- Large cargo volume
- More productivity thanks to high payload of 55.0 tons
- The tarpaulin cover can be operated from both sides via handwheels



Payload

Load limits		A	B	C	D
	S	39,0 t	45,2 t	47,0 t	55,0 t
	120	00,0 t			

Tare weight 25'000 kg

Dimensions

Length over buffers 14.04 m

Distance between outer wheelsets 10.80 m

Track gauge 1'435 mm

Minimum radius 75 m

Axle load 22.6 t

Carriage height above rail top edge 3.440 mm

Container capacity 75 m³

Container material Unalloyed structural steel 1.0038

Technical data

UIC-Profile RIV

Brake KE-GP

Bogie Y25 CS

Buffer Group A, UIC 526-1

Sicherheitselemente optional Derailment detector

Optional

Ausrüstung

Untergestell	Welded frame construction, quality CT2 and CT3
Sidewall thickness	4 Millimeters
Stirnwanddicke	4 Millimeters
Bodendicke	6 Millimeters
Türdicke	5 Millimeters
Planverdeck	PVC-coated synthetic fiber fabric

Covered wagon with tarpaulin top, 75m³, Tams

