wascosa

Pocket wagon T4.2, Sdgnss

for the transport of trailers, high volume containers and swap-bodies



Advantages

- Flexible loading options for the majority of trailer and container sizes
- Support frame improved automatic locking of the height adjustment
- Weight and load-optimized
- Low maintenance

Payload

Load limits

					_
	А	В	С	D	
S	43,8 t	51,8 t	61,8 t	69,8 t	***
SS	43,8 t	51,8 t	59	,8 t	

Wagen marking

C P	P	h			(P)
	+6	SNC	/ DB / NS / B / GC (SJ) / DSB) / NSB	SBB / DB / NS / SNCB / GC (SJ) / DK (DSB) / NSB	+6
	0		SNCF / PKP / / ÖBB	FS / PKP / CFL / ÖBB	0


Tare weight	20′200 kg
Max. brake weight	72 t
Handbrake weight	20 t

Dimensions	
Length over buffers	20′000 mm
Loading length	18'400 mm
Distance between bogie centers	14′200 mm
Axles base in bogie	1′800 mm
Height of loading stack over rail	270 mm
Height of load platform over rail	1'155 mm
Saddle height for trailer	980 mm, 1'130 mm
Track gauge	1′435 mm


Technical data	
Bogie	2 x Y25 Ls(s)i1 1 x Y25 Ls(s)i1(f) with handbrake
Axle load	22,5 t
Brake	KNORR KE-GP-A
Brake blocks	Jurid 816 M BG (320 mm)
Buffers	UIC 520-4, Kat. A

RIV, UIC 505-1
The trailer is set down with its kingpin on the support frame (heights 980 mm / 1,130 mm) of the pocket wagon. The kingpin locks automatically. The support frame is located on a head piece and can be moved longitudinally from each side of the trolley using a hand wrench and can therefore be adapted to different trailer lengths. When no in use, it is locked over the head piece. The axles of the trailer are set down in the wheel recess.
The wagon is equipped with 26 container spigots, 24 hinged pins and 2 hinged support plates (support für 40' containers). 2 spigots on the non-support side are permanently welded on.
75 m
150 m
1°30′





• Note: Wagons may not be loaded with semi-trailers if the support frame deadline has expired!





Wascosa AG T +41 41 727 67 67 Werftestrasse 4 info@wascosa.com CH-6005 Luzern www.wascosa.com