

## Silo wagon, dusty goods, 70 m<sup>3</sup>, Uacns



### Advantages

- Self-supporting superstructure without longitudinal beams
- Therefore low dead weight
- More productivity thanks to high payload of 69.4 tons



### Payload

Load limits		A	B	C	D
	S	46,4 t	47,1 t	51,4 t	69,4 t
	120	00,0 t			

Tare weight 20'600 kg

### Dimensions

Length over buffers 13.54 m

Distance between outer wheelsets 10.30 m

Track gauge 1'435 mm

Minimum radius 35 m

Axle load 22.5 t

Tank capacity 70 m<sup>3</sup>

Tank material S355J2G3

Discharge pressure 2,0 bar

### Technical data

UIC-Profile RIV

Brake DK-GP-A 2x9" (K)

Bogie Y25 Lsi(f)-K

Buffers Group A, UIC 526-1

Safety elements, optional Derailment detector

Optional

### Equipment

Fixed clutch	Storz, DN125
Blindkupplung	Storz, DN125
Dome cover	Ø570 x 20, AW5083-0
Non-return valve	DN50/PN16
Shut-off flap	DN125/PN16
Dom slider	DN500

## Equipment

2 outlet cones with	shut-off valves DN 200
Outlet pipe with	DN 100 (on both sides)
Ferry boat angle	2°30'

## Silo wagon, dusty goods, 70 m<sup>3</sup>, Uacns

